

Fuel Schedule – 2025

Month	Number	Type	Dispatch Date	Closing Date
January	M986 A386 D344	Motor Gasoline, RBOB Aviation Gasoline, 100LL Ultra Low Sulfur Diesel	November 22	January 10
February	M987 F322 T349	Motor Gasoline, RBOB Fuel Oil, Type 2 Turbine Fuel, Kerosine	December 27	February 14
March	M988 D345 T350	Motor Gasoline, Ethanol blended Ultra Low Sulfur Diesel Turbine Fuel, Kerosine	January 24	March 14
April	M989 F323 T351	Motor Gasoline, Premium Fuel Oil, Type 2 Turbine Fuel, Kerosine	February 21	April 11
May	M990 D346 F324	Motor Gasoline, Ethanol Blended ULSD B5 Blend Fuel Oil, Type 2	March 21	May 9
June	M991 F325 T352	Motor Gasoline, Ethanol blend Fuel Oil, Type 2 Turbine Fuel, Kerosine	April 25	June 13
July	M992 A387 D347	Motor Gasoline, Premium Aviation Gasoline, 100LL ULSD B5 Blend	May 23	July 11
August	M993 F326 T353	Motor Gasoline, Premium Fuel Oil, Type 2 Turbine Fuel, Kerosine	June 20	August 8
September	M994 D348 T354	Motor Gasoline, CBOB Ultra Low Sulfur Diesel Turbine Fuel, Kerosine	July 25	September 12
October	M995 F327 T355	Motor Gasoline, Premium Fuel Oil, Type 2 Turbine Fuel, Kerosine	August 22	October 10
November	M996 D349 F328	Motor Gasoline, Ethanol Blended ULSD B5 Blend Fuel Oil, Type 2	September 26	November 14
December	M997 D350 T356	Motor Gasoline, Premium Ultra Low Sulfur Diesel Turbine Fuel, Kerosine	October 24	December 12

Test methods refer to latest ASTM or CGSB revision unless otherwise specified.

InnoTech Alberta, Applied Chemistry Services, 250 Karl Clark Road, Edmonton, Alberta, Canada, T6N 1E4

Phone: 780.450.5538 Fax: 780.988.9053 Email: exchange@innotechalberta.ca

Website: exchange.innotechalberta.ca

F110a-08

Page 1 of 4

Fuel Analysis Included – 2025

Aviation Gasoline			
ASTM D4052	Density at 15°C	ASTM D3338	Net Heat of Combustion
ASTM D86	Distillation Range	ASTM D2700	Octane Number, Motor
ASTM D381	Gum, Unwashed Content	ASTM D5453	Sulfur
ASTM D3341	Lead	ASTM D5191	Vapor Pressure

Aviation Turbine			
ASTM D3242	Acid Number	ASTM D3338	Net Heat of Combustion
ASTM D1319	Aromatics	ASTM D4529	Net Heat of Combustion
ASTM D6379	Aromatics	ASTM D1319	Olefins
ASTM D130	Corrosion, Copper	ASTM D1322	Smoke Point
ASTM D4052	Density at 15°C	ASTM D4294	Sulfur
ASTM D86	Distillation Range	ASTM D5453	Sulfur
ASTM D4952	Doctor Test	ASTM D7039	Sulfur
ASTM D2624	Electrical Conductivity at 20°C	All Methods	Sulfur
IP 540	Existent Gum Content	ASTM D3227	Sulfur, Mercaptan
ASTM D56	Flash Point	ASTM D3241	Thermal Oxidation Stability
ASTM D5972	Freezing Point	ASTM D445	Viscosity at -20°C
ASTM D3948	Micro Separometer	ASTM D7042	Viscosity at -20°C
ASTM D1840	Naphthalenes	ASTM D7224	Water Separation

Test methods refer to latest ASTM or CGSB revision unless otherwise specified.

InnoTech Alberta, Applied Chemistry Services, 250 Karl Clark Road, Edmonton, Alberta, Canada, T6N 1E4

Phone: 780.450.5538 Fax: 780.988.9053 Email: exchange@innotechalberta.ca

Website: exchange.innotechalberta.ca

F110a-08

Page 2 of 4

Fuel Analysis Included – 2025

Diesel Fuel			
ASTM D611	Aniline Point	ASTM D93	Flash Point, Procedure A
ASTM D7371	Biodiesel Content	ASTM D7094	Flash Point
ASTM D2887	Boiling Range Distribution	ASTM D6079	High Frequency Reciprocating Rig
ASTM D613	Cetane Number	CAN/CGSB-3.0 No. 140.1	Low Temperature Flow Test (LTFT)
ASTM D976	Cetane Index, Calculated	ASTM D97	Pour Point
ASTM D4737	Cetane Index, Calculated	ASTM D5949	Pour Point
ASTM D2500	Cloud Point	ASTM D5453	Sulfur
ASTM D5773	Cloud Point	ASTM D7039	Sulfur
ASTM D130	Corrosion, Copper	ASTM D445	Viscosity at 40°C
ASTM D4052	Density at 15°C	ASTM D7042	Viscosity at 40°C, Dynamic
ASTM D7042	Density at 40°C	ASTM D7042	Viscosity at 40°C, Kinematic
ASTM D86	Distillation Range	ASTM D6304	Water Content, Procedure A
ASTM D2624	Electrical Conductivity at 20°C		

Fuel Oil			
ASTM D664	Acid Number	ASTM D4629	Nitrogen
ASTM D2887	Boiling Range Distribution	ASTM D97	Pour Point
ASTM D4530	Carbon Residue, 10% Bottoms	ASTM D5949	Pour Point
ASTM D2500	Cloud Point	ASTM D5453	Sulfur
ASTM D5773	Cloud Point	ASTM D7039	Sulfur
ASTM D4052	Density at 15°C	ASTM D3227	Sulfur, Mercaptan
ASTM D86	Distillation Range	ASTM D445	Viscosity at 40°C
ASTM D93	Flash Point, Procedure A	ASTM D7042	Viscosity at 40°C, Kinematic
ASTM D7094	Flash Point		

Fuel Analysis Included – 2025

Motor Gasoline			
ASTM D1319	Aromatics	ASTM D381	Gum, Solvent Washed Content
CAN/CGSB-3.0 No. 14.3	Aromatics	ASTM D525	Induction Period at 100°C
CAN/CGSB-3.0 No. 14.3	Benzene	ASTM D2699	Octane Number, Research
Regulation SOR/97-493	Benzene Emission Number	ASTM D2700	Octane Number, Motor
ASTM D130	Corrosion, Copper	ASTM D1319	Olefins
CAN/CGSB-3.0 No. 60.32	Corrosion, Silver Wool	CAN/CGSB-3.0 No. 14.3	Olefins
ASTM D7671	Corrosiveness, Silver Strip	ASTM D5453	Sulfur
NACE TM0172	Corrosive Properties	ASTM D7039	Sulfur
ASTM D4052	Density at 15°C	ASTM D3227	Sulfur, Mercaptan
ASTM D86	Distillation Range	ASTM D5191	Vapor Pressure
CAN/CGSB-3.5	Driveability Index (Specification)	All methods	Oxygen Content
CAN/CGSB-3.511	Driveability Index (EtOH Corr.)	All methods	Ethanol
ASTM D381	Gum, Unwashed Content	All methods	Methanol

Fuel exchange test samples are provided in one 4 L epoxy lined metal can.